BASIC EMERGENCY PORTAL

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Rated power of the luminaire [W]*:	1.00
Luminous flux [lm]*:	164
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II
Energy efficiency class:	B
Material of the body:	PC
Diffuser material:	PC
Diffuser type:	transparent
Optics material:	PC
Optics:	reflector
Battery:	LiFePO4
Operating mode:	NM
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	280/185/55;

CHARACTERISTICS

The Emergency Portal is a versatile luminaire designed to illuminate open spaces and indicate evacuation routes using pictograms. The use of the latest-generation LEDs guarantees high energy efficiency and excellent illumination of escape routes. The advanced emergency module allows for manual or automatic testing, significantly facilitating ongoing diagnostics and monitoring of the luminaire's performance, whilst immediately signalling any faults or the need to replace the battery. The luminaire's elegance is emphasised by its slender, neutral and timeless design, whilst its flexible construction allows for easy installation, whether wall-mounted or ceiling-mounted.

APPLICATION

The high IP54 protection rating effectively protects the luminaire against dust and moisture, enabling it to operate reliably in industrial, warehouse and technical environments. At the same time, the modern design of the housing ensures that the Emergency Portal fits perfectly into the aesthetics of public and commercial buildings — such as offices, restaurants, hotels and shopping centres. The luminaire is the ideal solution for lighting open areas and passageways required by fire safety regulations.

BASIC EMERGENCY PORTAL

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Emergency lighting [h]	Operating mode	Autotest	Light distribution type	Dimensions (H/W/T/S) [mm]	Ingress protection	Mounting version	Index
1	4000	164	transparent	1	NM	yes	general	280/185/55	IP54	surface	>> 736681
1	4000	164	transparent	1	NM	yes		280/185/55	IP54	surface	>> 736698

Card creation date: 13 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 98/2026

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl