VIGO M LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	30.00 - 200.00
Luminous flux [lm]*:	2800 - 19000

CHARACTERISTICS

Energy-saving floodlight with LED sources. The lampshade made out of highly-permeable PMMA and linear lenses influence the excellent light parameters of the floodlight. Solid construction and connector grants it high ingress protection IP65, and aluminium body and diffuser made out of PMMA - grants high impact resistance IK10. The metal mounting arm with angle adjustment enables precise direction of the flow of light. The luminaire should not be used in places that use mechanical devices that may endanger human health.

APPLICATION

This luminaire is intended for illumination of facades, large billboards and for industry.

VIGO M LED

GENERAL CARD


AVAILABLE VERSIONS

Click index >>, to see details

VIGO M LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



VIGO M LED

Card creation date: 29 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 100/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl