POXAR SN-F LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Nominal power [W]:	1.00
Material of the body:	PC
Diffuser material:	PMMA
Working temperature [°C]:	from 0 to +35
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	299/206/43;

CHARACTERISTICS

Surface mounted emergency fitting with a power of 1W, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, battery life in the event of emergency is 3h. NiCd battery life in the event of emergency is 3h. A bracket for wall mounting available on request.

APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended in for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

POXAR SN-F LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Emergency lighting [h]	Index
1	3	>> 324543

Card creation date: 01 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 68/2020

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl