

# LUMAX S LED

GENERAL CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP40
Nominal power [W]:	2.00
Diffuser material:	PC
Diffuser type:	PRM
Working temperature [°C]:	from 0 to +35
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	350/120/75;

## CHARACTERISTICS

Surface-mounted, universal (maintained or non-maintained system) emergency fitting with a low profile including an integrated, energy-saving LED light source with a power of 2W. Body made of plastic, grey; prismatic polycarbonate (PC) diffuser. NiCd battery with manual testing function included; battery life in the event of emergency is 3h. Usable visibility of exit signs – up to 20 meters.

## APPLICATION

Autonomous emergency fitting, dedicated for illumination of evacuation routes and emergency exits in the event of voltage drop in the power grid, i.e. in emergency mode. Product intended for surface mounting walls. Recommended particularly for areas of technical nature (passageways, staircases, garages, cellars) and for all applications which require the installation of permanent emergency lighting.

# LUMAX S LED

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Diffuser type	Emergency lighting [h]	Index
2	PRM	3	<a href="#">&gt;&gt; 323829</a>

Card creation date: 01 August 2023  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 67/2020



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)