

POINT LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	8.00
Luminous flux [lm]*:	770 - 930
Colour temperature [K]:	3000; 4000
SDCM:	≤ 3
Energy efficiency class:	D; E
Material of the body:	PP
Diffuser material:	glass
Diffuser type:	OPAL; PRM
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	ø230/90;

CHARACTERISTICS

Surface-mounted, round LED light fixture with high luminous flux, ingress protection class IP44 and an integrated energy-saving light source LED. White base made of polypropylene; opal or prismatic glass diffuser. Available with a radio motion sensor (RCR).

APPLICATION

surface mounted luminaire for mounting on ceilings and walls; intended both for indoor (maintenance rooms, passageways) and outdoor use (façade lighting). The version with a radio motion sensor (RCR) is particularly well-suited to be used as a light source for public rooms and buildings (civic buildings, apartment buildings).

POINT LED

GENERAL CARD

AVAILABLE VERSIONS




Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Energy efficiency class	Index
8	3000	770	OPAL		E	>> 225116
8	4000	810	OPAL		E	>> 225123
8	3000	770	OPAL	yes	E	>> 225246
8	4000	810	OPAL	yes	E	>> 225253
8	3000	850	PRM		E	>> 225130
8	4000	930	PRM		D	>> 225147
8	3000	850	PRM	yes	E	>> 225222
8	4000	930	PRM	yes	D	>> 225239


POINT LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



Point LED 8W OPAL 4000K



POINT LED 8W PRM 4000K

Card creation date: 01 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 403/2023; 77/2013



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl