

# CAMEA LED EVO 2

---

GENERAL CARD



## TECHNICAL PARAMETERS

---

Luminous flux [lm]\*: 770 - 1750

## CHARACTERISTICS

---

Surface-mounted, round LED light fixture with integrated energy-saving light source LED, high luminous flux, and high ingress protection class IP44. Base and ring made of UV-resistant plastic. A specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10). Available in four ring colours. Optional equipment: radio motion sensor (RCR). Colour temperature 3000K/4000K, CRI>80, lifespan of LED 50 000h (L70B50) ta= 25 °C.

## APPLICATION

---

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

# CAMEA LED EVO 2

---

GENERAL CARD

## AVAILABLE VERSIONS

---




Click index >>, to see details


# CAMEA LED EVO 2

## GENERAL CARD

### LUMINOUS INTENSITY DISTRIB. CURVE



CAMEA LED EVO 10W 4000K




CAMEA LED EVO 20W 4000K

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 15/2022; 16/2022; 28/2018



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl