CAMEA LED LC

GENERAL CARD

TECHNICAL PARAMETERS

Nominal power [W]:	9.00 - 16.00
Luminous flux [lm]*:	920 - 2150

CHARACTERISTICS

Surface-mounted, round LED light fixture with high luminous flux, ingress protection class IP44, and an integrated energy-saving lights source LED. Base and ring made of UV-resistant plastic. A specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

CAMEA LED LC

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

CAMEA LED LC

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



CAMEA LED 9W 4000

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 397/2023; 73/2017

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl