

# UP LED

---

GENERAL CARD



## TECHNICAL PARAMETERS

---

**Luminous flux [lm]\*:** 220 - 240

## CHARACTERISTICS

---

Energy-saving, outdoor 2W accent fitting provides economical and long-term operation without replacing light sources. Dustproof and waterproof luminaire with an ingress protection class of IP65, protected against dust and water splashing from a nozzle directed at any angle. Available with asymmetrical light distribution. Specification: color temperature of the LED light source: 3000K, 4000K.

## APPLICATION

---

Outdoor luminaire intended to illuminate facades, stairs, alcoves, pillars and greenery in gardens, parks and recreational facilities.

# UP LED

---

GENERAL CARD

## AVAILABLE VERSIONS

---




[Click index >>, to see details](#)

# UP LED

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



UP LED rozsyl

Card creation date: 21 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 187/2023; 57/2015



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl