VEGA LED

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK08
Nominal power [W]:	7.00
Luminous flux [lm]*:	880; 920
Colour temperature [K]:	4000
SDCM:	5
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	glass
Diffuser type:	OPAL; PRM
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	239/95;
Warranty [years]:	2

CHARACTERISTICS

LED light fixture with integrated energy-saving light source LED and high ingress protection class IP44. Base made of UV-resistant plastic. Diffuser made of PC, available in 2 versions: opalized or prismatic.

APPLICATION

Surface-mounted fitting with an ingress protection class of IP44 dedicated for both outdoor and indoor use.

VEGA LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
7	4000	880	OPAL	E	>> 950537
7	4000	920	PRM	E	>> 950520

Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 394/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl