

# LUNGO LED

GENERAL CARD



## TECHNICAL PARAMETERS

|                                   |  |
|-----------------------------------|--|
| <b>Light source:</b>              | COB LED                                      |
| <b>Ingress protection:</b>        | IP20   |
| <b>Nominal power [W]:</b>         | 10.00  |
| <b>Luminous flux [lm]*:</b>       | 825; 860                                     |
| <b>Colour temperature [K]:</b>    | 3000   |
| <b>Colour rendering index:</b>    | >80  |
| <b>Energy efficiency class:</b>   | F  |
| <b>Material of the body:</b>      | aluminium                                    |
| <b>Colour of the body:</b>        | aluminium; black; black-gold; white          |
| <b>Diffuser material:</b>         | PMMA   |
| <b>Diffuser type:</b>             | PRM  |
| <b>Optics material:</b>           | PMMA   |
| <b>Optics:</b>                    | lens   |
| <b>Mounting version:</b>          | surface; suspended                           |
| <b>Working temperature [°C]:</b>  | from -20 to +35                              |
| <b>Supply voltage [V]:</b>        | 220-240                                      |
| <b>Frequency [Hz]:</b>            | 50 - 60                                      |
| <b>Dimensions (H/W/T/S) [mm]:</b> | 60/145; 60/145/1500;<br>60/250; 60/250/1500; |

## CHARACTERISTICS

The family of lungo luminaires will make each interior stylish and original. The option to combine different sizes and colours of luminaires allows creating original compositions which will be a decorative embellishment of rooms arranged in a modern way.

## APPLICATION

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

# LUNGO LED

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### LUNGO LED surface

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Beam angle [°] | Colour of the body | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index                           |
|-------------------|------------------------|---------------------|----------------|--------------------|---------------------------|-------------------------|---------------------------------|
| 10                | 3000                   | 825                 | 24             | aluminium          | 60/145                    | F                       | <a href="#">&gt;&gt; 645600</a> |
| 10                | 3000                   | 825                 | 24             | white              | 60/145                    | F                       | <a href="#">&gt;&gt; 645594</a> |
| 10                | 3000                   | 825                 | 24             | black-gold         | 60/145                    | F                       | <a href="#">&gt;&gt; 645587</a> |
| 10                | 3000                   | 825                 | 24             | black              | 60/145                    | F                       | <a href="#">&gt;&gt; 645570</a> |
| 10                | 3000                   | 825                 | 50             | aluminium          | 60/145                    | F                       | <a href="#">&gt;&gt; 645259</a> |
| 10                | 3000                   | 825                 | 50             | white              | 60/145                    | F                       | <a href="#">&gt;&gt; 645211</a> |
| 10                | 3000                   | 825                 | 50             | black-gold         | 60/145                    | F                       | <a href="#">&gt;&gt; 645228</a> |
| 10                | 3000                   | 860                 | 50             | black              | 60/145                    | F                       | <a href="#">&gt;&gt; 645242</a> |
| 10                | 3000                   | 825                 | 24             | aluminium          | 60/250                    | F                       | <a href="#">&gt;&gt; 645563</a> |
| 10                | 3000                   | 825                 | 24             | white              | 60/250                    | F                       | <a href="#">&gt;&gt; 645556</a> |
| 10                | 3000                   | 825                 | 24             | black-gold         | 60/250                    | F                       | <a href="#">&gt;&gt; 645549</a> |
| 10                | 3000                   | 825                 | 24             | black              | 60/250                    | F                       | <a href="#">&gt;&gt; 645532</a> |
| 10                | 3000                   | 825                 | 50             | aluminium          | 60/250                    | F                       | <a href="#">&gt;&gt; 645334</a> |
| 10                | 3000                   | 825                 | 50             | white              | 60/250                    | F                       | <a href="#">&gt;&gt; 645303</a> |
| 10                | 3000                   | 825                 | 50             | black-gold         | 60/250                    | F                       | <a href="#">&gt;&gt; 645310</a> |
| 10                | 3000                   | 825                 | 50             | black              | 60/250                    | F                       | <a href="#">&gt;&gt; 645327</a> |

### LUNGO LED suspended

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Beam angle [°] | Colour of the body | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index                           |
|-------------------|------------------------|---------------------|----------------|--------------------|---------------------------|-------------------------|---------------------------------|
| 10                | 3000                   | 825                 | 24             | aluminium          | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645631</a> |
| 10                | 3000                   | 825                 | 24             | white              | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645617</a> |
| 10                | 3000                   | 825                 | 24             | black-gold         | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645624</a> |
| 10                | 3000                   | 825                 | 24             | black              | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645860</a> |
| 10                | 3000                   | 825                 | 50             | aluminium          | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645297</a> |
| 10                | 3000                   | 825                 | 50             | white              | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645266</a> |
| 10                | 3000                   | 825                 | 50             | black-gold         | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645273</a> |
| 10                | 3000                   | 825                 | 50             | black              | 60/145/1500               | F                       | <a href="#">&gt;&gt; 645280</a> |
| 10                | 3000                   | 825                 | 24             | aluminium          | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645679</a> |
| 10                | 3000                   | 825                 | 24             | white              | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645655</a> |
| 10                | 3000                   | 825                 | 24             | black-gold         | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645662</a> |
| 10                | 3000                   | 825                 | 24             | black              | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645648</a> |
| 10                | 3000                   | 825                 | 50             | aluminium          | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645853</a> |
| 10                | 3000                   | 825                 | 50             | white              | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645341</a> |
| 10                | 3000                   | 825                 | 50             | black-gold         | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645358</a> |

# LUNGO LED

---


## GENERAL CARD

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Beam angle [°] | Colour of the body | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index                           |
|-------------------|------------------------|---------------------|----------------|--------------------|---------------------------|-------------------------|---------------------------------|
| 10                | 3000                   | 825                 | 50             | black              | 60/250/1500               | F                       | <a href="#">&gt;&gt; 645365</a> |


# LUNGO LED

## GENERAL CARD

### LUMINOUS INTENSITY DISTRIB. CURVE



LUNGO 825lm 24D 250mm  
ALUMINIUM 830 (10W)



LUNGO 825lm 50D 145mm  
ALUMINIUM 830 (10W)

Card creation date: 26 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 161/2019; 229/2023