

CORPACT LED



220-240 V
50-60 Hz

LED



TECHNICAL PARAMETERS

Ingress protection:	IP40/20;
Nominal power [W]:	24.00 - 60.00
Luminous flux [lm]*:	2300 - 6000
Colour rendering index:	>80;
SDCM:	≤ 3;
Energy efficiency class:	A+; A;
Material of the body:	ABS;
Diffuser material:	PMMA;
Diffuser type:	OPAL;
Mounting version:	recessed;
Dimensions [mm]:	595/595/93;

*Tolerance +/- 10%

CHARACTERISTICS

CORPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

AVAILABLE TYPES

[Click >> index, to see details](#)

CORPACT LED 24W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Energy efficiency class	Index
24	3000	2300	OPAL		A+	>> 658594
24	4000	2500	OPAL		A+	>> 658600
24	3000	2300	OPAL	yes	A+	>> 658655
24	4000	2500	OPAL	yes	A+	>> 658662

CORPACT LED 42W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Energy efficiency class	Index
42	3000	3750	OPAL		A	>> 658617
42	4000	4050	OPAL		A+	>> 658624
42	3000	3750	OPAL	yes	A	>> 658679
42	4000	4050	OPAL	yes	A+	>> 658686

CORPACT LED 60W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Energy efficiency class	Index
60	3000	5300	OPAL		A	>> 658631
60	4000	6000	OPAL		A+	>> 658648
60	3000	5300	OPAL	yes	A	>> 658693
60	4000	6000	OPAL	yes	A+	>> 658709

*Tolerance +/- 10%

ACCESSORIES

Name	Index
plasterboard recessing kit 630x630 white	999543

plasterboard recessing kit
630x630 white (999543)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-05-13



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



27/2019