NECTRA LED PLUS

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP44
Nominal power [W]:	5.00 - 25.00
Luminous flux [lm]*:	500 - 3450
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
Energy efficiency class:	D; E; F
Material of the body:	PC + aluminium
Diffuser material:	PMMA
Diffuser type:	OPAL
Optics material:	aluminium
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	ø222/70; ø170/69; ø121/67;
Warranty [years]:	2 / 0.5 (bateria); 5

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation.
Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

NECTRA LED PLUS 5W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
5	3000	500	OPAL	yes	ø121/67	F	>> 517853
5	3000	500	OPAL	yes	ø121/67	F	>> 517815
5	3000	500	OPAL		ø121/67	F	>> 517792
5	3000	500	OPAL		ø121/67	F	>> 517839
5	4000	540	OPAL		ø121/67	F	>> 517822
5	4000	540	OPAL	yes	ø121/67	F	>> 517846
5	4000	540	OPAL	yes	ø121/67	F	>> 517808
5	4000	540	OPAL		ø121/67	F	>> 517785

NECTRA LED PLUS 9W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
9	3000	860	OPAL		ø121/67	F	>> 517754
9	3000	860	OPAL	yes	ø121/67	F	>> 517778
9	3000	860	OPAL	yes	ø121/67	F	>> 517730
9	3000	860	OPAL		ø121/67	F	>> 517716
9	4000	930	OPAL		ø121/67	F	>> 517709
9	4000	930	OPAL	yes	ø121/67	F	>> 517723
9	4000	930	OPAL	yes	ø121/67	F	>> 517761
9	4000	930	OPAL		ø121/67	F	>> 517747

NECTRA LED PLUS 12W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
12	3000	1550	OPAL		ø170/69	E	>> 517679
12	3000	1550	OPAL	yes	ø170/69	E	>> 517693
12	3000	1550	OPAL	yes	ø170/69	E	>> 517655
12	3000	1550	OPAL		ø170/69	E	>> 517631
12	4000	1650	OPAL		ø170/69	D	>> 517662
12	4000	1650	OPAL	yes	ø170/69	D	>> 517686
12	4000	1650	OPAL	yes	ø170/69	D	>> 517648
12	4000	1650	OPAL		ø170/69	D	>> 517624

NECTRA LED PLUS 15W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1950	OPAL		ø170/69	E	>> 517594
15	3000	1950	OPAL	yes	ø170/69	E	>> 517617

NECTRA LED PLUS

GENERAL CARD

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
15	3000	1950	OPAL	yes	ø170/69	E	>> 517570
15	3000	1950	OPAL		ø170/69	E	>> 517556
15	4000	2100	OPAL		ø170/69	D	>> 517587
15	4000	2100	OPAL		ø170/69	D	>> 517549
15	4000	2100	OPAL	yes	ø170/69	D	>> 517600
15	4000	2100	OPAL	yes	ø170/69	D	>> 517563
15	3000	2000	OPAL		ø222/70	D	>> 517518
15	3000	2000	OPAL	yes	ø222/70	D	>> 517532
15	3000	2000	OPAL	yes	ø222/70	D	>> 517495
15	3000	2000	OPAL		ø222/70	D	>> 517471
15	4000	2150	OPAL		ø222/70	D	>> 517501
15	4000	2150	OPAL	yes	ø222/70	D	>> 517525
15	4000	2150	OPAL		ø222/70	D	>> 517464

NECTRA LED PLUS 20W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
20	3000	2500	OPAL		ø222/70	E	>> 517396
20	3000	2500	OPAL	yes	ø222/70	E	>> 517419
20	3000	2500	OPAL	yes	ø222/70	E	>> 517457
20	3000	2500	OPAL		ø222/70	E	>> 517433
20	4000	2700	OPAL		ø222/70	D	>> 517426
20	4000	2700	OPAL	yes	ø222/70	D	>> 517440
20	4000	2700	OPAL	yes	ø222/70	D	>> 517402
20	4000	2700	OPAL		ø222/70	D	>> 517389

NECTRA LED PLUS 25W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
25	3000	3250	OPAL		ø222/70	D	>> 517358
25	3000	3250	OPAL	yes	ø222/70	D	>> 517372
25	3000	3250	OPAL	yes	ø222/70	D	>> 517334
25	3000	3250	OPAL		ø222/70	D	>> 517310
25	4000	3450	OPAL		ø222/70	D	>> 517341
25	4000	3450	OPAL	yes	ø222/70	D	>> 517365
25	4000	3450	OPAL	yes	ø222/70	D	>> 517327
25	4000	3450	OPAL		ø222/70	D	>> 517303

Card creation date: 22 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 340/2023; 60/2020

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl