GAMMA LED BASIC

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	10.00 - 16.00
Luminous flux [lm]*:	1240 - 2100
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	D; E
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL
Optics material:	PC
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	ø280/72;
Warranty [years]:	5

CHARACTERISTICS

The latest version of our bestseller - even better performance, same proven quality.
Surface-mounted, round LED light fitting, ingress protection class IP54, and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.
The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

GAMMA LED BASIC

GENERAL CARD

AVAILABLE VERSIONS


Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Version	PIR	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
10	4000	1240	OPAL				czarny RAL9005	ø280/72	>> 327230
10	4000	1240	OPAL				white	ø280/72	>> 191374
10	4000	1240	OPAL			yes	white	ø280/72	>> 192289
10	4000	1240	OPAL	yes	RCR Merrytek		white	ø280/72	>> 191404
10	4000	1240	OPAL	yes	RCR Hytronik		white	ø280/72	>> 192180
10	4000	1240	OPAL	yes	RCR Merrytek		czarny RAL9005	ø280/72	>> 327261
14	4000	1650	OPAL				czarny RAL9005	ø280/72	>> 327247
14	4000	1650	OPAL				white	ø280/72	>> 191381
14	4000	1650	OPAL			yes	white	ø280/72	>> 192296
14	4000	1650	OPAL	yes	RCR Merrytek		czarny RAL9005	ø280/72	>> 327278
14	4000	1650	OPAL	yes	RCR Hytronik		white	ø280/72	>> 192197
14	4000	1650	OPAL	yes	RCR Merrytek		white	ø280/72	>> 191411
16	4000	2100	OPAL				czarny RAL9005	ø280/72	>> 327254
16	4000	2100	OPAL			yes	white	ø280/72	>> 192302
16	4000	2100	OPAL				white	ø280/72	>> 191398
16	4000	2100	OPAL	yes	RCR Merrytek		czarny RAL9005	ø280/72	>> 327285
16	4000	2100	OPAL	yes	RCR Hytronik		white	ø280/72	>> 192203
16	4000	2100	OPAL	yes	RCR Merrytek		white	ø280/72	>> 191428

GAMMA LED BASIC

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE




GAMMA LED

GAMMA LED BASIC

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WSE0005	RC MOS MR004 IoT programming remote control



RC MOS MR004 IoT programming remote control (WSE0005)

Card creation date: 29 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: max 392/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl