



TECHNICAL PARAMETERS

Nominal power [W]:	28.00 - 77.00
Luminous flux [lm]*:	2350 - 5700

CHARACTERISTICS

Recessed modular fitting with an integrated energy-saving LED panel, made of white powder-coated steel. Opal diffuser made of polystyrene ensures even light distribution. The fitting's central part is a blende, which is a component of a modular ceiling. Due to it the fitting can be perfectly matched with the interior's design.

APPLICATION

Multipurpose fitting intended for mounting in modular ceilings in offices, representative rooms or rooms of general use. It can be also used as the main light source and it is suitable for work requiring sight focus. The fitting will be perfect as a new application or while replacing the traditional fluorescent fittings with energy-saving LED solutions.

ARTO LED


GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

LUMINOUS INTENSITY DISTRIB. CURVE




ARTO LED 30W 4000K

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 27 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 142/2017; 143/2017; 144/2017