# DL 220 LED

GENERAL CARD



## TECHNICAL PARAMETERS

## CHARACTERISTICS

Round LED downlight recessed mounting, even light distribution and high ingress protection class IP65 (diffuser), IP40 (top) equipped with an integrated energy-saving light source LED Body made of ABS plastic with prismatic PC diffuser. Available options with DALI/DIMM 1-10V or with emergency module. Colour temperature 3000K/4000K, CRI>80, LED lifespan 50 000h (L70B50) ta= 25 ºC.

## APPLICATION

The luminaire is intended for both internal (offices, passageways, utility rooms) as well as external use. Especially recommended for lighting public facilities, including hospital & educational facilities, offices, halls, garages, passageways, warehouses, shops as well as in the food industry, commercial and service facilities related to food goods. Thanks to the possibility of using ballasts compatible with DALI control systems, it is especially recommended for class A office buildings. It provides good surface illumination and supports work requiring high eyesight concentration. It has been designed for installation in any type of suspended ceiling (modular, plasterboard).

# DL 220 LED

GENERAL CARD

## AVAILABLE VERSIONS




Click index >>, to see details

# DL 220 LED

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE




DL 220 40W 4000K 1

Card creation date: 31 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 114/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl